

LM 1200 - 2000 - 2500 - 3000 - 4000 - 4500

CARATTERISTICHE TECNICHE DONNEES TECHNIQUES SPECIFICATIONS CARACTERISTICAS TECNICAS	LM 1200	LM 2000	LM 2500	LM 3000	LM 4000	LM 4500
CAPACITA' TAMBORO CAPACITE DU TAMBOUR DRUM CAPACITY CAPACIDAD TAMBOR	1.200 Lt	2.000 Lt	2.500 Lt	3.000 Lt	4.000 Lt	4.500 Lt
RESA PER IMPASTO CAPACITE' DE BETON COMPACTE READY MIXED CONCRETE CAPACIDAD EFECTIVA HORMIGON	1000 Lt	1.600 Lt	2.000 Lt	2.400 Lt	3.000 Lt	3.500 Lt
CAPACITA' BENNA MORDENTE CAPACITE' DE LA BENNE BUCKET CAPACITY CAPACIDAD BIVALVA DE CARGA	90 Lt	170 Lt	170 Lt	270 Lt	270 Lt	270 Lt
CAPACITA' SERBATOIO ACQUA CAPACITE' RESERVOIR EAU WATER TANK CAPACITY CAPACIDAD DEPOSITO AGUA	170 Lt	230 Lt	280 Lt	650 Lt	650 Lt	650 Lt
PESO A VUOTO POIDS A VIDE UNLOADED WEIGHT PESO EN VACIO	2.450 Kg	3.500 Kg	3.750 Kg	5.600 Kg	6.000 Kg	6.450 Kg
PORTATA MAX PORTEE MAX MAX PAYLOAD CARGA MAXIMA	2.450 Kg	3.500 Kg	4.800 Kg	5.500 Kg	6.500 Kg	7.700 Kg
TRASMISSIONE TRANSMISSION TRANSMISION	MECCANICA/IDROSTATICA MECANIQUE/HIDROSTATIQUE MECHANICAL/HYDROSTATIC MECANICA/HYDROSTATICA	MECCANICA MECANIQUE MECHANICAL MECANICA	MECCANICA/IDROSTATICA MECANIQUE/HIDROSTATIQUE MECHANICAL/HYDROSTATIC MECANICA/HYDROSTATICA	MECCANICA/IDROSTATICA MECANIQUE/HIDROSTATIQUE MECHANICAL/HYDROSTATIC MECANICA/HYDROSTATICA	IDROSTATICA HIDROSTATIQUE HYDROSTATIC HYDROSTATICA	IDROSTATICA HIDROSTATIQUE HYDROSTATIC HYDROSTATICA
MARCE AVANTI / RETRO VITESSE AV/AR FORWARD / REVERSE GEARS VELOCIDADES ADELANTE / ATRAS	4/4 - 2/2	4/4	4/4 - 2/2	4/4 - 2/2	2/2	2/2
VELOCITA' MAX VITESSE MAX MAX SPEED VELOCIDAD MAX	22 Km/h	22 Km/h	22 Km/h	25 Km/h	25 Km/h	25 Km/h
PENDENZA SUPERABILE A PIENO CARICO PENTE MAX. A PLEIN CHARGE MAX GRADIENT AT FULL LOAD PENDIENTE MAXIMA	30 %	30 %	30 %	30 %	30 %	30 %
FRENI FREINS BRAKES FRENOS	A TAMBORO A TAMBOUR BRAKE DRUMS DE TAMBOR	A TAMBORO A TAMBOUR BRAKE DRUMS DE TAMBOR	A DISCO A DISQUES BRAKE DISCS A DISCO	A DISCO A DISQUES BRAKE DISCS A DISCO	A DISCO A DISQUES BRAKE DISCS A DISCO	A DISCO A DISQUES BRAKE DISCS A DISCO
PNEUMATICI PNEUS TYRES NEUMATICOS	11,5 / 80-15,3	10,5 / 80-18	12,0 / 75-18	12,5 / 80-18	12,5 / 80-18	405/70 R20" 14 PR
MOTORE - MOTEUR - ENGINE - MOTOR DIESEL						
POTENZA MAX PUISSANCE MAX. MAX RATING POTENCIA HP	HP 36/51	Hp 54,4	Hp 54,4/63	Hp 78/102	Hp 102	Hp 102
Nr. CILINDRI Nr. CYLINDRES Nr CYLINDERS Nr. CILINDROS	3/4	3	3	4	4	4
SISTEMA DI RAFFREDDAMENTO REFROIDISSEMENT COOLING SYSTEM SISTEMA DE REFRIGERATION	ACQUA EAU WATER AGUA	ARIA AIR AIRE	ARIA/ACQUA AIR/EAU AIR/WATER AIRE/AGUA	ARIA/ACQUA AIR/EAU AIR/WATER AIRE/AGUA	ACQUA EAU WATER AGUA	ACQUA EAU WATER AGUA
CAPACITA' SERBATOIO CARBURANTE CAPACITE RESERVOIR CAARBURANT FUEL TANK CAPACITY CAPACIDAD DEPOSITO COMBUSTIBLE	30 Lt	30 Lt	30 Lt	55 Lt	55 Lt	55 Lt



BMT
EXPORT

Made in Italy



BMT
EXPORT

Made in Italy

LM 1200-2000-2500-3000-4000-4500



**AUTOBETONIERA
AUTOBETONNIERE
SELF LOADING MIXER
AUTOHORMIGONERAS**